



Product Data Sheet

Q-5000 HI STRENGTH HI TEMP CONTACT ADH.

Fast Tack, High Solids, High Strength, High Shear

Features

- Fast Tack, High Shear
- Quick Tack Formula
- No Oxone Depleting Substances
- Water-Resistant Bond
- Great On Various Substrates



Description

Quality Aerosols Q-5000 Contact is a high strength, high shear and fast tack adhesive. Our adhesive is specially formulated for making permanent bonds. Our Q-5000 is best best effective when both surfaces are coated. It can be used on many substrates such as wood, particle board, plywood, FRP board, Plastics, fiberglass insulation and many other surfaces. It has high solids and has a water resistant bond, quick tack and high temperature resistance. All surfaces should be tested for compatibility before using.

Applications

Used for the permanent bonding of wood, particle board, plywood, FRP Board, Plastics fiberglass insulation and other substrates.

Product Usage

Q-5000 Adhesive is designed to be applied to the two surfaces about to be joined, Spray an even coat of adhesive to cover 80% to 100% of the surfaces. Do not wet the surfaces. Allow to dry 2 to 5 minutes and becomes tacky. For porous surfaces it is recommended to apply a second coat after the first has become tacky. Put the coated surfaces together and apply pressure. Full adhesive strength will be reached in 24 hours.

For More Innovative Products from Quality Aerosols

Visit us at www.qualityaerosols.com

Health	2
Flammability	3
Reactivity	0
Personal Protection	A



Product Specifications

Color	Clear to Yellow or Red
Odor	Typical Solvent Odor
Solids	30% +/- 2%
pH	N/A
Specific Gravity	1.04 g/cc +/- 0.02 g/cc
Physical State	Liquid
% VOC	12% / 241 g/l
Evaporation Rate	Not determined
Boiling Point	156°F
Flash Point	138°F
Spray Pattern	Web
Storage	Store in a cool, dry, and well-ventilated area. Do not handle or store near open flame or other sources
Sizes Offered	20 oz, 11#,38#, 177#,355#
Net Weight	17oz, 11#, 37.5#, 187#, 369#
VOC Compliant OTC	Yes
Ozone Depleting Compounds	No
Shelf Life	1 Year +
Square Feet Coverage	20oz - approx 51 ft2 @ 2.5gms 11# - approx 527 ft2 @ 2.5gms 38# - approx 1798 ft2 @ 2.5gms 177# - approx 8967 ft2@2.5gms 355# - approx 17690 ft2@2.5gm
Note:All results are based on 2.5gms dried glue/ft2	

Transportation Information

Proper Shipping Name	Liquefied Gas, Flammable NOS
	UN3161, Class 2.1
24 hr. Medical Emergency	1-800-424-9300 US 1-703-527-3887 International

Q-5000
Hi Strength
Contact Adhesive