



Product Data Sheet

Q-5021 CALIFORNIA COMPLIANT CONTACT ADHESIVE

Air Assist, California Compliant Contact

Features

- Fast Tack, Great for Multiple Substrates
- Quick Tack Formula
- No Ozone Depleting Substances
- Water-Resistant Bond
- Can Be Sold and Used in the SCAQMD



Description

Quality Aerosols Q-5021 Air Assisted California Complaint Contact is a high strength, high shear, fast tack adhesive developed exclusively for use with a pressure pot air system. Our Q-5021 Air Assisted Adhesive is best effective when both surfaces are coated. It can be used on wood, particle board, plywood, FRP board, Plastics, fiberglass insulation and many other surfaces. It has high solids and has a water resistant bond, quick tack and high temperature resistance. All surfaces should be tested for compatibility before using.

Applications

Used for the permanent bonding of wood, particle board, plywood, FRP Board, Plastics fiberglass insulation and other substrates.

Product Usage

Q-5021 Adhesive is designed to be applied to the two surfaces about to be joined, Spray an even coat of adhesive to cover 80% to 100% of the surfaces. Do not wet the surfaces. Allow to dry 2 to 5 minutes and becomes tacky. For porous surfaces it is recommended to apply a second coat after the first has become tacky. Put the coated surfaces together and apply pressure. Full adhesive strength will be reached in 24 hours.

For More Innovative Products from Quality Aerosols
Visit us at www.qualityaerosols.com

Health	2
Flammability	3
Reactivity	0
Personal Protection	A



Q-5021 Air Assist
Compliant Contact

Product Specifications

Color	Clear to Yellow or Red
Odor	Typical Solvent Odor
Solids	38.4% +/- 2 %
pH	N/A
Specific Gravity	0.948 g/cc +/- 0.02 g/cc
Physical State	Liquid
% VOC	3.27%/14.1 g/l
Evaporation Rate	Not determined
Boiling Point	156°F
Flash Point	138°F
Spray Pattern	Web
Storage	Store in a cool, dry, and well-ventilated area. Do not handle or store near open flame or other sources
Sizes Offered	11#, 38#, 177#, 355#
Net Weight	9#, 27#, 135#, 270#
VOC Compliant CARB/OTC	Yes
Ozone Depleting Compounds	No
Shelf Life	1 Year +
Square Feet Coverage	11#-approx 621 ft2 @ 2.5gms 38#-approx 1863 ft2 @2.5gms
Note:*All results are based on 2.5gms dried glue/ft2	177#-approx 9321 ft2@2.5gms 355#-approx 18650 ft2@2.5gm
Transportation Information	
Proper Shipping Name	Non Flammable NOS
	UN1956, Class 2.2
24 hr. Medical Emergency	1-800-424-9300 US 1-703-527-3887 International