



Product Data Sheet

Q-5300 NON-FLAMMABLE CONTACT ADHESIVE

Fast Tack, High Solids, High Strength, High Shear

Features

- Fast Tack, High Shear
- Completely Non-Flammable
- No Ozone Depleting Substances
- Water-Resistant Bond
- Great On Various Substrates



Description

Quality Aerosols Q-5300 Contact is a high strength, high shear and fast tack adhesive. Our adhesive is specially formulated for making permanent bonds. Our Q-5300 is best best effective when both surfaces are coated. It can be used on many substrates such as wood, particle board, plywood, FRP board, fiberglass insulation and many other surfaces. It has high solids and has a water resistant bond, quick tack and high temperature resistance. All surfaces should be tested for compatibility before using.

Applications

Used for the permanent bonding of wood, particle board, plywood, FRP Board, most fiberglass insulations and other substrates.

Product Usage

Q-5300 Adhesive is designed to be applied to the two surfaces about to be joined, Spray an even coat of adhesive to cover 80% to 100% of the surfaces. Do not wet the surfaces. Allow to dry 2 to 5 minutes and becomes tacky. For porous surfaces it is recommended to apply a second coat after the first has become tacky. Put the coated surfaces together and apply pressure. Full adhesive strength will be reached in 24 hours.

For More Innovative Products from Quality Aerosols

Visit us at www.qualityaerosols.com

Health	2
Flammability	0
Reactivity	1
Personal Protection	A



Product Specifications

Color	Clear to Yellow or Red
Odor	Sweet Pungent
Solids	30% +/- 2%
pH	N/A
Specific Gravity	1.18 g/cc +/- 0.02 g/cc
Physical State	Liquid
% VOC	2% / g/l
Evaporation Rate	Not determined
Boiling Point	156°F
Flash Point	138°F
Spray Pattern	Web
Storage	Store in a cool, dry, and well-ventilated area. Do not handle or store near open flame or other sources
Sizes Offered	11#,38#, 177#,355#
Net Weight	11#, 37.5#, 187#, 369#
VOC Compliant OTC	Yes
Ozone Depleting Compounds	No
Shelf Life	1 Year +
Square feet coverage	11# - approx 527 ft ² @ 2.5gms
Note:*All results are based	38# - approx 1798 ft ² @ 2.5gms
on 2.5gms dried glue/ft ²	177# - approx 8967 ft ² @2.5gms
	355# - approx 17690 ft ² @2.5gm
Transportation Information	
Proper Shipping Name	
11# & Larger	UN3500, Chem under press, 2.2
24 hr. Medical Emergency	1-800-424-9300 US 1-703-527-3887 International

Q-5300 Non-Flammable Contact