



Product Data Sheet

Q-6000 PRESSURE SENSITIVE ADHESIVE

High Solids, High Strength, Strong Shear & Peel Strength

Features

- High Strength, High Shear
- Re-Positionable Formula
- No Ozone Depleting Substances
- Water-Resistant Bond
- Great On Various Substrates



Description

Quality Aerosols Q-6000 Pressure Sensitive is a high strength, high shear adhesive. Our adhesive is specially formulated for making temporary or permanent bonds. Our Q-6000 is best effective when both surfaces are coated, but for most applications only one substrate will need to be coated. It has high solids, high strength, strong shear and peel strength along with high temperature resistance. All substrates should be tested for compatibility before using.

Applications

Q-6000 is designed for applications requiring soft glue lines, strong shear, peel strength and has the ability to re-position before bonding. Great on open weave fabrics

Product Usage

Q-6000 Adhesive is designed to be applied to the one or two surfaces about to be joined. Spray an even coat of adhesive to cover 80% to 100% of the surfaces. Do not wet the surfaces. Allow to dry 2 to 5 minutes and becomes tacky. For porous surfaces it is recommended to apply a second coat after the first has become tacky. Put the coated surfaces together and apply pressure. Full adhesive strength will be reached in 24 hours.

For More Innovative Products from Quality Aerosols
Visit us at www.qualityaerosols.com

Health	2
Flammability	3
Reactivity	0
Personal Protection	A



Product Specifications

Color	Clear to Yellow or Red
Odor	Typical Solvent Odor
Solids	28% +/- 2%
Heat Resistance	200°F
Specific Gravity	1.18 g/cc +/- 0.02 g/cc
Physical State	Liquid
% VOC	30% / 304 g/l
Evaporation Rate	Not determined
Boiling Point	NA
Flash Point	138°F
Spray Pattern	Web
Storage	Store in a cool, dry, and well-ventilated area. Do not handle or store near open flame or other sources
Sizes Offered	20 oz, 11#, 38#, 177#, 355#
Net Weight	17oz, 9#, 37.5#, 185#, 375#
VOC Compliant OTC	Yes
Ozone Depleting Compounds	No
Shelf Life	1 Year +
Square Feet Coverage	20oz - approx 51 ft ² @ 2.5gms 11# - approx 527 ft ² @ 2.5gms
Note: All results are based on 2.5gms dried glue/ft ²	38# - approx 1798 ft ² @ 2.5gms 177# - approx 8967 ft ² @2.5gms 355# - approx 17690 ft ² @2.5gm

Transportation Information

Proper Shipping Name	Liquefied Gas, Flammable NOS
	UN3161, Class 2.1
24 hr. Medical Emergency	1-800-424-9300 US 1-703-527-3887 International

Q-6000
Hi Strength Pressure
Sensitive Adhesive