



Product Data Sheet

Q-6200 VOC COMPLIANT PRESSURE SENSITIVE

Non-Chlorinated, Low VOC, California VOC Compliant, Fast Tack

Features

- High Temperature Resistance to Shear Failure
- Re-Positionable Formula
- No Ozone Depleting Substances
- Water-Resistant Bond
- VOC Compliant in all states plus California



Description

Quality Aerosols Q-6200 is a non-chlorinated Pressure Sensitive adhesive. It is designed to bond fabric, foam, plywood and other light substrates onto various surfaces, such as fiberglass metal, most plastics, wood and many more. It is fast drying ideal for many rigid and non rigid substrates, both porous and non-porous surfaces. It is excellent as a pressure sensitive adhesive when used on a one sided application for temporary bonds and repositionability but also works great as a contact adhesive when used on a two sided application for permanent bonds.

Applications

Q-6200 is designed for applications requiring temporary or permanent bonds. Is excellent for carpet where strong shear strength and peel strength along with the ability to re-position the substrate is necessary before bonding.

Product Usage

Q-6200 Adhesive is designed to be applied to the one or two surfaces about to be joined. Spray an even coat of adhesive to cover 80% to 100% of the surfaces. Do not wet the surfaces. Allow to dry 2 to 5 minutes and becomes tacky. For porous surfaces it is recommended to apply a second coat after the first has become tacky. Put the coated surfaces together and apply pressure. Full adhesive strength will be reached in 24 hours.

For More Innovative Products from Quality Aerosols

Visit us at www.qualityaerosols.com

Health	2
Flammability	4
Reactivity	1
Personal Protection	A



Product Specifications

Color	Clear to Yellow or Red
Odor	Typical Solvent Odor
Solids	28% +/-2%
Heat Resistance	200°F
Specific Gravity	0.95 gms/cc +/- 0.02 gms/cc
Physical State	Liquid
% VOC	0.5%/17 g/l
Evaporation Rate	Not determined
Heat Resistance	200°F
Flash Point	156°F
Spray Pattern	Semi-Web Lacy Spray
Storage	Store in a cool, dry, and well-ventilated area. Do not handle or store near open flame or other sources
Sizes Offered	20 oz, 11#, 38#, 177#, 355#
Net Weight	12oz, 8#, 27#, 130#, 260#
VOC Compliant OTC & CA.	Yes
Ozone Depleting Compounds	No
Shelf Life	1 Year +
Square Feet Coverage	20oz - approx 37 ft ² @ 2.0 gms
	11# - approx 398 ft ² @ 2.0 gms
Note: All results are based	38# - approx 1,240 ft ² @ 2.0 gms
on 2.0gms dried glue/ft ²	177# - approx 6,452 ft ² @2.0 gms
	355# - approx 12,903 ft ² @2.0 gm

Transportation Information

Proper Shipping Name	Liquefied Gas, Flammable NOS
	UN3161, Class 2.1
24 hr. Medical Emergency	1-800-424-9300 US
	1-703-527-3887 International

Q-6200
VOC Compliant
Pressure Sensitive
Adhesive