



Product Data Sheet

PAINT & GASKET REMOVER

Powerful Clinging Gel

#QUA01173



Features

- Spray On - Let Set - Scrape Off
- Excellent for Gasket Removal
- Great on Appliances, Automobiles, Machinery
- OK To Flush Away With Water
- Very Easy To Use

Description

Quality Aerosols Paint and Gasket Remover is a powerful clinging gel that quickly blisters lacquers, enamels, shellacs and acrylics. This product can be used on plaster, wood, metal, masonry, stone or ceramics. Blistered paint can be scraped off or flushed away with water.

Applications

Used for removal of gaskets, paint, varnish, shellac, adhesive and many other uses.

Directions

Shake can before use for approximately 30 seconds. Clean off dirt, grease or heavy soil. Make certain surface is dry. To avoid possible skin contact, do not stand downwind of spray or mist during application. Hold can 8 to 10 " from surface. Apply a heavy, even coat to entire surface. Allow product to remain on surface for several minutes, even after blistering action has occurred. Remove residue with a scraper, putty knife, cloth or strong water spray. If necessary, repeat application after surface is dry.

For More Innovative Products from Quality Aerosols

Visit us at www.qualityaerosols.com

Health	2
Flammability	2
Reactivity	0
Personal Protection	B



Product Specifications

Color	Cloudy
Odor	Pungent
Solids	N/A
pH	N/A
Specific Gravity	1.32
Physical State	Liquid
% VOC	23.25%
Evaporation Rate	>1
Boiling Point	N/A
Flash Point	Concentrate: N/A Propellant -132.23°F
Storage	Store in a cool, dry, and well-ventilated area. Do not handle or store near open flame or other sources
Can Size	20 oz
Net Weight	18 oz
UPC Number	13964 55821
Spray Pattern	Tight Fan Spray
Shelf Life	1 Year +
VOC Compliant CARB/OTC	Yes
Recyclable Packaging	Yes
Ozone Depleting Compounds	No
Transportation Information	
Class #	55
Proper Shipping Name	Consumer Commodity, ORM-D
NMFC	48580-3
Shipping Weight	17.0 lbs
Packaged	12 cans per case
24 hr. Medical Emergency	1-800-424-9300 US 1-703-527-3887 International