



Product Data Sheet

GENERAL PURPOSE ADHESIVE

General Purpose, Repositionable Adhesive #QUA01211

Features

- Fast Tack, High Shear Strength Adhesive
- Formulated for Permanent or Temporary Bonds
- VOC Compliant - All States
- Is Repositionable With Soft Glue Lines
- Fast and Effective

Description

Quality Aerosols VOC Compliant Pressure Sensitive Adhesive is a general purpose adhesive with quick tack. Our adhesive is specially formulated for permanent or temporary bonding. Works on all substrates, such as wood, particle board, plywood and many other substrates. It can also be used for making permanent or temporary bonds to other compatible non-porous and porous substrates, like open cell foam, latex backed carpet and foam cork board. VOC Compliant in all states.

Applications

Used for the permanent or temporary bonding of wood, gaskets, cork, felt, fabric, paper, molded fiberglass, most plastics, fiberglass insulation board, duct liner and wrap or Molded PVC, closed & open cell foam, latex backed carpet and foam core board.

Directions

Shake can before use for approximately 60 seconds. Make sure surface is free of dust, dirt, oil, wax, rust and loose paint. Surface must be completely dry. Turn Applicator to the width of pattern required (High, Medium or Low). Spray both substrates and allow adhesive to cure (approximately 2-3 minutes). Then press both substrates together for approximately 3-5 minutes.

For More Innovative Products from Quality Aerosols

Visit us at www.qualityaerosols.com

| | |
|---------------------|---|
| Health | 2 |
| Flammability | 3 |
| Reactivity | 1 |
| Personal Protection | A |



Product Specifications

| | |
|-----------------------------------|---|
| Color | Natural |
| Odor | Sweet Pungent |
| Solids | 24-26% |
| pH | N/A |
| Specific Gravity | 0.74-0.78 |
| Physical State | Liquid |
| % VOC | 55% |
| Evaporation Rate | >1 |
| Boiling Point | N/A |
| Flash Point | Concentrate: -4°F Propellant -132.23°F |
| Storage | Store in a cool, dry, and well-ventilated area. Do not handle or store near open flame or other sources |
| Can Size | 20 oz |
| Net Weight | 14 oz |
| UPC Number | 13964 55851 |
| Spray Pattern | 2-5" Web |
| Shelf Life | 1 Year + |
| VOC Compliant CARB/OTC | Yes |
| Recyclable Packaging | Yes |
| Ozone Depleting Compounds | No |
| Transportation Information | |
| Class # | 55 |
| Proper Shipping Name | Consumer Commodity, ORM-D |
| NMFC | 48580-3 |
| Shipping Weight | 14.7 lbs |
| Packaged | 12 cans per case |
| 24 hr. Medical Emergency | 1-800-424-9300 US 1-703-527-3887 International |