



Product Data Sheet

Q2001 Wood Glue

Ease of Use, Uniform Results, High Solids

Q2001 Wood Glue

Features

- High Wet Tack
- Freeze-Thaw Stable (3 cycles)
- Fast Setting
- Good Heat and Solvent Resistance

Description

Quality Aerosols Q2001 has been specifically formulated for professional use. Q2001 can be used as a general purpose wood glue. It has a water-resistant bond. Do-it-yourself woodworkers benefit from the professional grade formula. Q2001 can be used on many different substrates, such as, wood, cloth, paper, leather and felt. Q2001 has a good heat and solvent resistance bond and a low chalk point.

Applications

Used for the permanent bonding of wood, particle board, plywood, hardboard, leather and felt.

Product Usage

Q2001 can be applied by any conventional method: roll coat, extruder, squeeze bottle or brush. Q2001 is used for permanently bonding wood, particle board and many other substrates. It is great for general woodwork gluing. Care should be taken to ensure that all components to be glued are approximately the same temperature and adequate time is given for bond to form. It is best used at room temperature, with lower temperatures having longer cure times. Clean up with water when wet, mild solvent when dry.

Storage

Store in a cool, dry, and well ventilated area. Do not handle or store near open flame or other heat sources. We recommend storing at or above 65°F. Bulk products should be kept off the floor.

For More Innovative Products from Quality Aerosols
Visit us at www.qualityaerosols.com

Product Specifications

Color	Yellow or White
Solids	46% +/- 2%
VOC Content	0%
VOC Compliant CARB/OTC	Yes
Application Method	Squeeze bottle, Roll or Brush
Sizes Offered	5 gal, 55 gal, 250 gal
Warranty Period	6 months from manufacture date
Chalking Temp.	48°-50° F
Recommended laydown	2-5 g/ft²

