



# Product Data Sheet

## Q5250 California Compliant Contact Adhesive

Fast Tack, High Solids, High Strength

# Q5250 California Compliant Contact Adhesive

### Features

- Fast Tack, Great for Multiple Substrates
- Quick Tack Formula
- Brush & Spray Grade
- Water-Resistant Bond
- No Chlorinated Solvents

### Description

Quality Aerosols Q5250 California Compliant Contact is a high temperature, high shear and fast tack adhesive. Our adhesive is specially formulated for making permanent bonds. Q5250 Adhesive is most effective when both surfaces are coated. It can be used on wood, particle board, plywood, FRP board, plastics, fiberglass insulation and many other surfaces. It has high solids, a water resistant bond, quick tack and high temperature resistance.

### Applications

Used for the permanent bonding of wood, particle board, plywood, FRP board, plastics, fiberglass insulation and other substrates.

### Product Usage

Q5250 Adhesive is designed to be applied to both surfaces to be joined. Both surfaces should be dry and clean of oil and debris. Spray an even coat of adhesive to cover 80%-100% of the surfaces. Do not wet the surfaces. Allow to dry 3-5 minutes to become tacky. For porous surfaces it is recommended to apply a second coat after the first has become tacky. Put the coated surfaces together and apply pressure. Full adhesive strength will be reached in 24 hours.

### Storage

Store in a cool, dry, and well ventilated area. Do not handle or store near open flame or other heat sources. We recommend storing at or above 65°F. Bulk products should be kept off the floor.

For More Innovative Products from Quality Aerosols  
Visit us at [www.qualityaerosols.com](http://www.qualityaerosols.com)

## Product Specifications

<b>Color</b>	Clear to Amber
<b>Solids</b>	42.6% +/- 2%
<b>VOC Content</b>	3.7% / 36 g/L
<b>VOC Compliant CARB/OTC</b>	Yes
<b>Bonding Range</b>	5-30 minutes
<b>Dry/Tack Time</b>	3-5 minutes
<b>Spray Pattern</b>	Bulk - Pattern depends on user
<b>Sizes Offered</b>	35#, 390#
<b>Warranty Period</b>	1 year from manufacture date
<b>Recommended laydown</b>	2.5 g/ft <sup>2</sup>

