

## **Product Data Sheet**

# **DRY MOLY**

# #QUA01172

## Non-Corrosive, Non-Conductive

#### **Features**

- Adheres to Metal, Rubber, Glass and Most Plastics
- Effective at Temperatures from -110°F to +1000°F
- Waterproof
- Withstands High Pressure
- Excellent for Anti-Seize and Anti-Friction



Quality Aerosols Dry Moly lubricant and coating is a superior long lasting dry lubricant that adheres to almost all materials. Withstands high temperatures and pressures. Repels dust and dirt and is resistant to water, alkalis and most acids. Greatly increases operating efficiency and reduces maintenance costs. Prevents corrosion seizing, wear galling, binding, sticking, chattering, squeaking and scraping. Designed for high pressure, load bearing applications. Excellent for anti-friction and anti-seize where a dust and dirt resistant dry lubricant is desirable.



Our Dry Moly works on almost all materials. Withstands temperature ranges from -110°F to 1000°F. Resists pressures up to 100,000 psi.

### **Directions**

Adheres to metal, rubber glass and most plastics

Effective at temperatures from -110°F to +1050°F

on-Corrosive, Non-Conductiv

and Waterproof

KEEP OUT OF REACH OF CHILDREN

12 OZ. NET WT. (340 GRAMS)

Shake can before use for approximately 30 seconds. Surface must be free from loose rust, oil, grease and old paint. Hold can 8-10 inches from surface and spray in a sweeping motion to insure a thin uniform coating. Allow first application to sit 3-5 minutes before applying second coat. IMPORTANT: To prevent clogging after each use invert can and spray a few short bursts to clear valve.

## For More Innovative Products from Quality Aerosols

Visit us at www.qualityaerosols.com

Health	2
Flammability	2
Reactivity	0
Personal Protection	A



### **Product Specifications**

Color	Charcoal	
Odor	Sweet Pungent	
Solids	N/A	
рН	N/A	
Specific Gravity	0.7865	
Physical State	Liquid	
% VOC	55.00%	
Evaporation Rate	>1	
Boiling Point	N/A	
Flash Point	Concentrate: -20°C	
	Propellant: -132.23°F	
Storage	Store in a cool, dry, and well-	
	ventilated area. Do not handle	
	or store near open flame or	
	other sources	
Can Size	16 oz	
Net Weight	12 oz	
UPC Number	13964 55822	
Spray Pattern	Tight Mist to Stream	
Shelf Life	1 Year +	
VOC Compliant CARB/OTC	Yes	
Recyclable Packaging	Yes	
Ozone Depleting Compounds	No	
Transportation Information		
Class #	55	
Proper Shipping Name	Consumer Commodity, ORM-D	
NMFC	48580-3	
Shipping Weight	13.0 lbs	
Packaged	12 cans per case	
	•	
24 hr. Medical Emergency	1-800-424-9300 US	
	1-703-527-3887 International	

Quality Aerosols • 313 Bell Park Drive • Woodstock, GA 30188 • 1-877-320-4747 • www.qualityaerosols.com 2/2012