



Product Data Sheet

Q8005 California Compliant Contact Adhesive Bulk High Strength, High Shear, Fast Tack

Q8005 California Compliant Contact Adhesive Bulk

Features

- Fast Tack, Great for Multiple Substrates
- Quick Tack Formula
- No Ozone Depleting Substances
- Water-Resistant Bond
- Meets and Exceeds the SCAQMD Rule 1168

Description

Quality Aerosols Q8005 California Compliant Contact Adhesive is a high strength, high shear and fast tack adhesive. It is specially formulated for making permanent bonds. Q8005 can be used on wood, particle board, plywood, FRP board, plastics, fiberglass insulation and many other substrates. It is a high solids adhesive with a quick tack time. Q8005 Adhesive is resistant to high temperatures and has a water resistant bond.

Applications

Q8005 is used for the permanent bonding of wood, particle board, plywood, FRP board, plastics, fiberglass insulation and many other substrates.

Product Usage

Q8005 Adhesive is designed as a two surface bonding application. All surfaces should be test for compatibility. Surfaces should be dry and clean of oil and debris. Spray, roll or brush an even coat of adhesive to cover 80%-100% of the surfaces. Allow solvents to dry 3-5 minutes until the adhesive becomes tacky. For porous surfaces it is recommended to apply a second coat after the first coat has become tacky. Put the coated surfaces together and apply pressure. Full adhesive strength will be reached in 24 hours.

Storage

Store in a cool, dry, and well ventilated area. Do not handle or store near open flame or other heat sources. We recommend storing at or above 65°F. bulk and canister products should be kept off the floor.

For More Innovative Products from Quality Aerosols
Visit us at www.qualityaerosols.com

Product Specifications

Color	Clear or Red
Solids	38.0% +/- 2%
VOC g/L	3.3% / 31.9 g/L
VOC Compliant CARB/OTC	Yes
Bonding Range	3-30 minutes
Dry/Tack Time	3-5 minutes
Application Method	Spray, Roll, or Brush
Sizes Offered	5 gallon, 55 gallon
Warranty Period	1 year from manufacture date
Square Feet Coverage	5 gal - approx 1863 ft ² @ 2.5g 55 gal - approx 18,650 ft ² @ 2.5g

Note: all results are based on 2.5g dried glue/ft²

