

Product Data Sheet

Q313 Multi-Purpose Mist Adhesive

Fast Tack, Mist Spray, Long Working Time, Cost Effective

Features

- Designed to Bond Various Substrates and Surfaces
- Long open time
- High temperature resistance to shear failure
- Fast drying and aggressive bonding strength
- Great for permanent and temporary bonds

Description

Quality Aerosols Q313 is a non-chlorinated, multi-purpose mist adhesive that can be used for many types of substrates and surfaces and will give you a very aggressive, permanent or temporary bond. Q313 is a versatile adhesive that can be used virtually on any substrate, such as paper, cardboard, fabric, foam, wood and many plastics. It has a fast drying time and is great for use in arts and crafts projects.

Applications

Used for permanent or temporary bonding of paper, cardboard, fabric, foam, wood and many plastics. Q313 is fast drying and has a very aggessive bonding tendency.

Product Usage

Q313 will give a permanent bond when applied to both surfaces to be joined, or a temporary bond when applied to only one side. Surfaces need to be dry and free of oil and debris. Spray an even coat of adhesive to cover 80%-100% of the surfaces. Allow to dry 2-4 minutes. For crucial areas it is recommended to apply a coat to both surfaces for a great bond. For best results spray on the first coat of adhesive and let it get tacky and then spray a second coat. This will allow for a great permanent bond. Best to use when the temperature is 70°F or higher.

Storage

Store in a cool, dry, and well ventilated area. Do not handle or store near open flame or other heat sources. We recommend storing at or above 65°F. Bulk and canister products should be kept off the floor.

For More Innovative Products from Quality Aerosols
Visit us at www.qualityaerosols.com

Product Specifications

 Color
 Clear to Slightly Amber

 Solids
 22.1% +/- 2%

 VOC Content
 64.1% / 448.3 g/L

VOC Compliant CARB/OTC No

Bonding Range 2-30 minutes
Dry/Tack Time 2-4 minutes

Spray Pattern Mist

Sizes Offered 12oz, 8#, 30#, 135#, 270# Warranty Period 1 year from manufacture date

Recommended layout 2.5 g/ft²

Note: all results are based on 2g dried glue/ft2

